



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

SECTION 1. IDENTIFICATION

Product name : Zerex™ Original Green 50/50 Antifreeze Coolant

Product code : 896524

Manufacturer or supplier's details

Company name of supplier : Valvoline Global Operations

Address : 100 Valvoline Way
Lexington, KY 40509
United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvolineglobal.com

Emergency telephone number : +1-800-VALVOLINE (+1-800-825-8654)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity (Oral) : Category 4

Reproductive toxicity : Category 1B

Specific target organ toxicity
- repeated exposure (Oral) : Category 2 (Kidney)

Other hazards

None known.

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H360 May damage fertility or the unborn child.
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Components

Chemical name	CAS No./Unique ID	Concentration (% w/w)
ethanediol	107-21-1*	>= 30 - <= 60
2,2' -oxybisethanol	111-46-6*	>= 1 - <= 5
disodium tetraborate pentahydrate	12179-04-3*	>= 0.1 - <= 1

* Indicates that the identifier is a CAS No.

SECTION 4. FIRST AID MEASURES

General advice

:

Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled

:

If unconscious, place in recovery position and seek medical advice.

If symptoms persist, call a physician.

In case of eye contact

:

Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

If swallowed	: If eye irritation persists, consult a specialist. : Keep respiratory tract clear. : Do NOT induce vomiting. : Do not give milk or alcoholic beverages. : Never give anything by mouth to an unconscious person. : If symptoms persist, call a physician. : Take victim immediately to hospital.
Most important symptoms and effects, both acute and delayed	: No symptoms known or expected. : Harmful if swallowed. : May damage fertility or the unborn child. : May cause damage to organs through prolonged or repeated exposure if swallowed.
Notes to physician	: No hazards which require special first aid measures. : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: No hazardous combustion products are known
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment.
Environmental precautions	: Prevent product from entering drains. : Prevent further leakage or spillage if safe to do so. : If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethanediol	107-21-1	TWA (Vapour)	25 ppm	ACGIH
		STEL (Vapour)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
2,2' -oxybisethanol	111-46-6	TWA	10 mg/m3	US WEEL
disodium tetraborate pentahydrate	12179-04-3	TWA	1 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

		TWA (Inhalable particulate matter)	2 mg/m3 (Borate)	ACGIH
		STEL (Inhalable particulate matter)	6 mg/m3 (Borate)	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 1.0719 g/cm3 (60.1 °F / 15.6 °C)



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available
Oxidizing properties	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: excessive heat
Incompatible materials	: Aldehydes Alkali metals Alkaline earth metals aluminum Lead sodium Strong acids strong bases Strong oxidizing agents Sulphur compounds Zinc Peroxides
Hazardous decomposition products	: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Harmful if swallowed.

Product:

Acute oral toxicity	: Acute toxicity estimate: 958.92 mg/kg Method: Calculation method
---------------------	---



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Components:

ethanediol:

- Acute oral toxicity : LD0 (Human): estimated 1.56 g/kg
Assessment: The component/mixture is moderately toxic after single ingestion.
- Acute inhalation toxicity : LC50 (Rat): 10.9 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): 9,530 mg/kg
- Acute toxicity (other routes of administration) : LD50 (Rat): 5,010 mg/kg
Application Route: Intraperitoneal
LD50 (Rat): 3,260 mg/kg
Application Route: Intravenous

2,2' -oxybisethanol:

- Acute oral toxicity : LD50 (Human): Expected 1,120 mg/kg
Target Organs: Kidney
- Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

disodium tetraborate pentahydrate:

- Acute oral toxicity : LD50 (Rat): 3,200 - 3,400 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 2.0 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Not classified due to lack of data.

Components:

ethanediol:



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Species : Rabbit
Result : No skin irritation

2,2' -oxybisethanol:

Species : Human
Result : Slight, transient irritation

disodium tetraborate pentahydrate:

Result : No skin irritation

Serious eye damage/eye irritation

Not classified due to lack of data.

Components:

ethanediol:

Result : Slight, transient irritation

2,2' -oxybisethanol:

Species : Rabbit
Result : Slight, transient irritation

disodium tetraborate pentahydrate:

Species : Rabbit
Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified due to lack of data.

Respiratory sensitisation

Not classified due to lack of data.

Components:

ethanediol:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

2,2' -oxybisethanol:

Test Type : Maximisation Test
Species : Guinea pig
Method : Directive 67/548/EEC, Annex V, B.6.
Result : Did not cause sensitisation on laboratory animals.



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

disodium tetraborate pentahydrate:

Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

ethanediol:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

2,2' -oxybisethanol:

Genotoxicity in vitro : Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Species: Mouse
Method: OECD Test Guideline 474
Result: negative
GLP: yes

Carcinogenicity

Not classified due to lack of data.

IARC Group 2A: Probably carcinogenic to humans
sodium nitrate 7631-99-4
(nitrate (ingested) under conditions that result in endogenous nitrosation)

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

May damage fertility or the unborn child.



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Components:

disodium tetraborate pentahydrate:

Reproductive toxicity - : Clear evidence of adverse effects on sexual function and
Assessment fertility, and/or on development, based on animal experiments

STOT - single exposure

Not classified due to lack of data.

STOT - repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Components:

ethanediol:

Exposure routes : Ingestion
Target Organs : Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Experience with human exposure

Components:

ethanediol:

Ingestion : Target Organs: Kidney

2,2' -oxybisethanol:

General Information : Liver
Kidney

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Components:

ethanediol:

- Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 27,540 mg/l
Exposure time: 96 h
Test Type: static test
- LC50 (Pimephales promelas (fathead minnow)): 8,050 mg/l
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l
End point: Growth inhibition
Exposure time: 7 d
- Toxicity to fish (Chronic toxicity) : NOEC (Pimephales promelas (fathead minnow)): 32,000 mg/l
Exposure time: 7 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 24,000 mg/l
Exposure time: 7 d

Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

2,2' -oxybisethanol:

- Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: DIN 38412

Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

disodium tetraborate pentahydrate:

- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Remarks: Information refers to the main component.



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Toxicity to algae/aquatic plants	: NOEC (Selenastrum capricornutum (green algae)): 118 mg/l End point: Growth inhibition Exposure time: 72 h Remarks: Information refers to the main component.
Toxicity to fish (Chronic toxicity)	: NOEC (Danio rerio (zebra fish)): 37.7 mg/l Exposure time: 34 d Remarks: Information refers to the main component.
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC (Daphnia (water flea)): 40 mg/l Exposure time: 21 d Remarks: Information refers to the main component.

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

Persistence and degradability

Components:

ethanediol:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 90 - 100 % Exposure time: 10 d Method: OECD Test Guideline 301
------------------	--

2,2' -oxybisethanol:

Biodegradability	: Result: Readily biodegradable. Biodegradation: 70 - 80 % Exposure time: 28 d Method: OECD Test Guideline 301B
------------------	--

Bioaccumulative potential

Components:

ethanediol:

Bioaccumulation	: Species: Crayfish (Procambarus) Bioconcentration factor (BCF): 0.27 Exposure time: 61 d Concentration: 1000 mg/l Method: Flow through
-----------------	---

Partition coefficient: n-octanol/water	: log Pow: -1.36
--	------------------

2,2' -oxybisethanol:



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100

Partition coefficient: n-octanol/water : log Pow: -1.47

disodium tetraborate pentahydrate:

Bioaccumulation : Remarks: Does not bioaccumulate.

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological information : No data available

Global warming potential

**Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the
United Nations Framework Convention on Climate Change (UNFCCC)**

Components:

octamethyltrisiloxane:

20-year global warming potential: 1.17
100-year global warming potential: 0.325
500-year global warming potential: 0.093
Atmospheric lifetime: 0.019 yr
Radiative efficiency: 0.06 Wm²ppb
Further information: Miscellaneous compounds

decamethylcyclopentasiloxane:

20-year global warming potential: 1.04
100-year global warming potential: 0.289
500-year global warming potential: 0.082
Atmospheric lifetime: 0.016 yr
Radiative efficiency: 0.098 Wm²ppb
Further information: Miscellaneous compounds



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

octamethylcyclotetrasiloxane [D4]:

20-year global warming potential: 2.66
100-year global warming potential: 0.739
500-year global warming potential: 0.211
Atmospheric lifetime: 0.027 yr
Radiative efficiency: 0.12 Wm²ppb
Further information: Miscellaneous compounds

dodecamethylcyclohexasiloxane:

20-year global warming potential: 0.51
100-year global warming potential: 0.142
500-year global warming potential: 0.04
Atmospheric lifetime: 0.011 yr
Radiative efficiency: 0.086 Wm²ppb
Further information: Miscellaneous compounds

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues	:	Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	:	Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methanol	67-56-1	100	100 (F003)

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Acute toxicity (any route of exposure)
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethanediol 107-21-1 >= 50 - < 70 %

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

ethanediol 107-21-1 >= 50 - < 70 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

ethanediol 107-21-1 >= 50 - < 70 %
2,2' -oxybisethanol 111-46-6 >= 1 - < 5 %

Clean Water Act

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

sodium hydroxide	1310-73-2	>= 0.1 - < 1 %
------------------	-----------	----------------

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

sodium hydroxide	1310-73-2	>= 0.1 - < 1 %
------------------	-----------	----------------

US State Regulations

Massachusetts Right To Know

ethanediol	107-21-1
water	7732-18-5

Pennsylvania Right To Know

ethanediol	107-21-1
water	7732-18-5
2,2' -oxybisethanol	111-46-6
sodium hydroxide	1310-73-2

Maine Chemicals of High Concern

water	7732-18-5
octamethylcyclotetrasiloxane [D4]	556-67-2

Vermont Chemicals of High Concern

ethanediol	107-21-1
water	7732-18-5
molybdic acid, disodium salt, dihydrate	10102-40-6
octamethylcyclotetrasiloxane [D4]	556-67-2

Washington Chemicals of High Concern

ethanediol	107-21-1
water	7732-18-5

California Prop. 65

WARNING: This product can expose you to chemicals including ethanediol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

ethanediol	107-21-1
------------	----------

California Permissible Exposure Limits for Chemical Contaminants

ethanediol	107-21-1
------------	----------

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : On the inventory, or in compliance with the inventory

CA. DSL : All components of this product are on the Canadian DSL



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

ENCS	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
US WEEL	:	USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / C	:	Ceiling limit
US WEEL / TWA	:	8-hr TWA

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 12/30/2025



SAFETY DATA SHEET

Zerex™ Original Green 50/50 Antifreeze Coolant

Version: 3.2

Revision Date: 12/30/2025

Print Date:
05/11/2026

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information : 000000154613